NP-KV30 Series

Compact and High Spec. Printer Module with built in control board.

Features

- · All in one, Super compact printer module: 119.6 x 118 x 81.4 mm
- Mechanism, auto-cutter, control board and interface are built-in.
- · High Speed printing up to 200 mm/sec.
- · Variety of paper holders (Standard to Extra Large size) are ready.





| Model name | NP-KV30UK | NP-KV30DK | NP-KV30BK |
|---------------------|---|--|---|
| Print method | Line thermal dot | | |
| Print speed | Max. 200 mm/sec | | |
| Dot density | 8 dots/mm (203 dpi) | | |
| Paper width | 80mm | | |
| Print width | 72mm | | |
| Paper diameter | Max. 90 mm (in case of using PH-10) | | |
| Barcode print | UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE128, CODE93, GS1 Data Bar, QR code (model 2) | | |
| | | | |
| Interface | USB (V2.0 FULL SPEED) | USB (V2.0 FULL SPEED) Serial (RS232C) | USB (V2.0 FULL SPEED) Serial (RS232C) Bluetooth |
| Power voltage | DC24V+- 5% | | |
| External dimensions | 119.6(W) x 118(D) x 81.4(H) mm | | |
| Weight | Approx. 580g | | |
| Cutting Method | Full cut & Partial cut (command selectable) | | |

*Notice • All features and specifications described are subject to change without prior notice.

MIPPON PRIMEX INC.

1-5-12 Unoki Ohtaku Tokyo 146-8650 JAPAN

Tel: +81 3 3750-5817 Fax:+81 3 3750-4555

E-mail: overseas@primex.co.jp
URL: http://www.primex.jp