



MP-B30 SERIES MOBILE PRINTER




Made for
 iPhone | iPad | iPod

MP-B30 SERIES

Mobile Printer

- Compact & Light Weight
- Drop rating: 1.8m (6feet), IP rating: IP54
- Printing Speed: 127mm/sec max
- Simple Operation & Stylish Design
- Optional Cradle for Charging

MP-B30
Cradle option



Measuring Instrument



PDA/ Smart Device



Barcode



Portable Printer



Medical Equipment

Model	MP-B20	
Printing	Method	Thermal line dot printing
	Number of dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	80 ⁺⁰ ₋₁
	Printing width (mm)	72
	Speed (mm/sec) max	127 (5inch)
	Outside diameter of paper roll (mm) max	Ø 51
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0	
Type of Paper	Roll paper	
Character type	Code page (17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character	
Bar code	UPC-A/E, JAN (EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar	
Power supply	Li-Ion Battery	
Communication interface	USB, Bluetooth®, W-LAN*1	
Input buffer	4K bytes	
Command	ESC/POS™ conformity	
Cutting method	Tear bar	
Falling resistance	1.8m ^{*2}	
IP rating	IP54 ^{*2}	
Operating temperature (°C)	-20 to 55	
Service life: Abrasion resistance (km)	50 ^{*3}	
Dimensions (W×D×H mm)	105 x 126 x 58 ^{*4}	
Mass (g)	395 ^{*5}	
Standard	FCC, CE, VCCI	
Bundled item	AC adapter, Battery, USB cable, Belt clip	
Option	Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap	
Software	Printer driver, OPOS, POS for .NET, Windows® CE (SDK), Android™ (SDK), iOS (SDK)	

*1 Selected model. *2 This number is test result based on SII procedures, not guaranteed value. *3 Use recommended thermal papers. *4 Excluding protrusion *5 with battery, without paper roll

ESC/POS™: Registered trademark of SEIKO EPSON CORP.
Windows® is the registered trademark of Microsoft Corporation(USA).

Android™ is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments GmbH

Siemensstraße 9, 63263 Neu-Isenburg, Germany
phone: +49-(0)6102-297-0 · Email: info@seiko-instruments.de
www.seiko-instruments.de